



SYNFORCE

lubricants



Australian made
Australian owned

HyGEAR MULTI UTTO


www.synforce.com.au

HyGEAR Multi, Universal Tractor Transmission Oil built on Group 2 base stocks using unique and advanced Technology Additives

Product Applications

Whether on the farm or on the job site, success requires equipment durability and performance. HyGEAR Multi uses a highly engineered UTTO additive technology offering proven protection for a wide range of applications, including:

- all tractor types
- combine harvesters
- sprayers
- selected construction equipment
- shipping container handler equipment



HyGEAR Multi offers the simplicity of a single fluid approach for:

- transmissions
- axles
- wet brakes
- hydraulic systems

Robust oxidative and thermal stability for;

- Prevention of oil thickening and the formation of harmful acidic deposits that can reduce heat transfer and efficiency
- Protection of critical components
- Reduced risk from seal leakage

Protection in the presence of water;

HyGEAR Multi provides protection for the tractor even in the presence of water. Many Other fluids on the market either do not provide any or the same level of protection in the presence of water as HyGEAR Multi

Dual wear system to provide;

- Protection for spur, helical, spiral bevel gears and bearings.
- Sensitivity for yellow metals in hydrostatic and hydraulic equipment.

Optimised friction system to provide;

- Good lock-up and holding capacity for clutches in transmission and Power Take-Off (PTO) systems
- Suppression of wet brake noise.
- Braking capacity for safe stopping within the design limits of the equipment

HyGEAR Multi meets or exceeds; API GL-4 .. CNH 3525=Ford M2C-134D = FNHA-201.00 .. FNHA- 2-C-200.00 .. John Deere JDM J20C, J20D .. Kubota UDT .. Massey Ferguson CMS M1145, M1143, M1141, M1135 VCE WB 101 ,WB 102 .. White Farm (AGCO) Q-186 .. ZF TE-ML 03E, 05F, 06R, 06K , 17E, 21FZF TE-ML 06E , 06N & 06F – Formulation specific .. Allison C-4 .. Valtra G2-08 .. Caterpillar TO-2 .. Fendt Vario .. CNH MAT 3540CNH MAT 3505 (MS1209) CNH MAT 3506 (MS1210) CNH MAT 3509 (MS1230) .. Same Deutz Fahr .. Landini .. Renault/ Claas .. Parker Denison UTTO/THF.. Hydraulic T6H20C .. Denison HF-0 .. Denison P-46 .. Vickers 35VQ25 .. JDQ 84 (& modified JDQ 84A)

Typical properties;

Viscosity @ 40 deg C, cSt	85.8
Viscosity @ 100 deg C, cSt	11.3
Viscosity Index	120
Density @ 15 deg C	0.88
SAE Grade	10w/30
Pour Point, deg C	-45

*“don't just change your oil,
change your expectations”*

