



Ashless G2-Fluids

Product codes s5132,46,68,90, March 25, 2009

DESCRIPTION

Synforce Ashless Fluids G2-32, G2-46, G2-68 and G2-90 are Zinc Free Ashless multifunctional lubricants formulated to satisfy the stringent demands required of Ashless Hydraulic Fluids and Rotary Screw Compressors fluids.

These fluids are formulated with 100% Hydro cracked Group 2 base oils and use the latest in additive technology to provide the following ...

- Very high performance Hydraulic and Compressor applications
- Very high oxidation stability (extended service life)
- High load carrying capacity
- Excellent demulsification
- Excellent corrosion protection against steel and non-ferrous metals
- Excellent filterability
- Excellent thermal and hydrolytic stability

Meets or Exceeds ;

For Hydraulic Fluids according to ...

Dennison HF-0, HF-1, HF-2,
DIN51524, part 2 and 3 (HLP, HVLP)
AFNOR NF E 48-603 (HM, HV)
VDMA 24318

Cincinnati Machine P-68, P-69, P-70
ISO 6743/4 (HM, HV)
SS 155434
U.S. Steel 126, 127 and 136

For Compressor oils according to ...

DIN 51506 (VBL, VCL, VDL)

ISO / DP 6521 (DAA, DAB, DAH, DAG)

Typical Specifications ;

	Iso 46	iso 68
Viscosity, cSt at 40 deg C	46	68
cSt at 100 deg C	7.2	9.3
Viscosity index	114	114

Also available in iso 32 and iso 90 or blended to required specification.

