



Ashless G2 Hydraulic Fluids

This product is not considered Hazardous according to criteria of "Worksafe Australia"

| | | |
|-----------------------------|--|-----------------|
| PRODUCT TYPE | Lubricating Oils, Anti Wear Hydraulic | |
| CHEMICAL DESCRIPTION | Petroleum derived Lubricating Oil | |
| INGREDIENTS | Refined mineral and chemical additives – not hazardous | |
| PHYSICAL DATA | Flash Point C | Typical > 200 C |
| | Boiling Point | >250°C |
| | Solubility in water | Negligible |

FIRE AND EXPLOSION HAZARD DATA:

Flash point over 170 C. Will not burn unless heated to high temperatures.

Extinguish fires with CO₂, Dry Chemical, Foam or BCF.

Fire fighters should wear self-contained breathing apparatus if fire is in poorly ventilated area and is too large for hand-held extinguisher.

HEALTH HAZARD DATA

| | |
|----------------------|--|
| EYE CONTACT: | May cause mild irritation |
| SKIN CONTACT: | May cause mild irritation |
| INHALATION: | May cause mild throat or nose irritation if inhaled at elevated temperatures |
| SWALLOWED: | May cause mild gastric irritation |

EMERGENCY AND FIRST AID PROCEDURES:

| | |
|----------------------|------------------------------------|
| EYE CONTACT: | Flush with water for 15-20 minutes |
| SKIN CONTACT: | Wash with soap and water |
| INHALATION: | Remove to fresh air |
| SWALLOWING: | Do not induce vomiting |

IN ALL CASES SEEK MEDICAL ATTENTION IF DISCOMFORT PERSISTS

| | |
|-------------------------|--|
| REACTIVITY DATA: | INCOMPATIBILITIES: Strong oxidisers |
| | Hazardous decomposition product |
| | Product is considered unstable |

SPILL OR LEAK PROCEDURE

Contain spill and shut off all sources of possible ignition
Absorb on fire retardant material, sand or earth.
Follow State or Local Authority regulations for disposal.

STORAGE AND HANDLING PROCEDURE

Not defined as Dangerous Goods for transport by road or rail.

Store away from heat, oxidizing agents, foodstuffs and clothing. No health risks are expected as a result of normal handling.

REFERENCE:

ISSUE DATE:
April 2011

FOR INFORMATION CONTACT:

Synforce (Aust.) Pty Ltd, P.O. Box 7181, Urangan, Hervey Bay, QLD. 4655
Telephone 07-41253531 Fax 07-41253521

Where the information provided in this bulletin indicates a potential hazard, adequate warning should be given to all

