



Diesel Mono 40

Product code s2214, June 10, 2004

Description

Synforce Diesel Mono 40 is a quality Monograde high-speed diesel engine oil. It is a low ash detergent oil which provides excellent wear resistance, high temperature stability with low temperature performance. The premium additive pack assures maximum protection against foaming and corrosion whilst maintaining engine cleanliness.

Mono 40 is suitable for use in on road transport, mining, marine, agricultural, earthmoving, stationary and construction equipment.

Mono 40 is a premium mono-grade engine oil for a wide range of both diesel and petrol engines, as well as some Hydraulic Transmission applications.

Recommendations

Mono 40 is recommended for use in both light and heavy-duty diesel engines and 4 stroke petrol engines where a mono-grade oil is preferred. These include naturally aspirated and turbocharged European, Japanese and pre-US diesel engines, operating under all conditions used in road transport, off-highway, marine and stationary plant and equipment.

Typical Characteristics

| | |
|-------------------------|-------|
| Viscosity cst @ 40° C, | 133.7 |
| Viscosity cst @ 100° C, | 14.6 |
| Viscosity Index | 110 |
| Sulphated Ash | 0.8 |

Meets or Exceeds

| | |
|----------------|--------------|
| Ford | M2C 121E3 |
| General Motors | 6094M, 6048M |
| Caterpillar | TO-2 |
| Mack | EO-K2 |
| Allison | C3 |
| Mercedes Benz | 228.0 |
| API | CF/SG |
| SAE | 40 |

