



GearSYN ZF7580

June 2012

Product;

GearSYN ZF7580 is a full PAO based synthetic manual transmission fluid formulated to meet the demanding requirements of heavy duty commercial manual and automated manual transmissions.

GearSYN ZF7580 offers oil drain intervals of up to 800,000 kilometres with ease of shifting and very high thermal durability.

Capabilities include broad synchromesh material compatibility allowing multi vehicle versatility, long oil life and optimum gear shifting.

Benefits

- Ideal for mixed fleet service fill applications
- OEM endorsed additive technology
- Long life of oil
- Proven performance for synchromesh, high loads and high temperatures.
- Clean internal surfaces of transmission

Recommendations;

GearSYN ZF7580 meets the requirements of ZF manual and automated manual transmissions as well as most manual transmissions found in heavy commercial vehicles requiring an SAE 75w/80 GL-4 synthetic lubricant.

GearSYN ZF7580 meets or exceeds the requirements of;

DAF ... Eaton ... IVECO ... MAN 341 Z-4/5 ... MAN 341 E3 ... MB 235.4 ... Renault ... Volvo 97305
ZF TE-ML 01E/L ... ZF TE-ML 02E/L ... ZF TE-ML 08 ... ZF TE-ML 16K/P ... API GL-4

<i>Typical properties;</i>	<i>Kinematic Viscosity @ 40°C,</i>	<i>96.9 cSt</i>
	<i>Kinematic Viscosity @ 100°C,</i>	<i>14.1 cSt</i>
	<i>Viscosity index</i>	<i>149</i>
	<i>Pour point</i>	<i>-54°C</i>
	<i>Specific gravity @ 15°C</i>	<i>0.847</i>
	<i>Colour</i>	<i>clear</i>

