



Moly D-3 Grease

This product is not considered Hazardous according to criteria of "Worksafe Australia"

| | | |
|-----------------------------|--|-----------------|
| PRODUCT TYPE | Lubricating Grease | |
| CHEMICAL DESCRIPTION | Petroleum derived Lubricating Grease | |
| INGREDIENTS | Refined mineral and chemical additives – not hazardous | |
| PHYSICAL DATA | Flash Point C | Typical > 150 C |
| | Boiling Point | NA |
| | Solubility in water | Negligible |

FIRE AND EXPLOSION HAZARD DATA:

Flash point over 150 C. Will not burn unless heated to high temperatures.

Extinguish fires with CO₂, Dry Chemical, Foam or BCF.

Fire fighters should wear self-contained breathing apparatus if fire is in poorly ventilated area and is too large for hand-held extinguisher.

HEALTH HAZARD DATA

| | |
|----------------------|--|
| EYE CONTACT: | May cause mild irritation |
| SKIN CONTACT: | May cause mild irritation |
| INHALATION: | May cause mild throat or nose irritation if inhaled at elevated temperatures |
| SWALLOWED: | May cause mild gastric irritation |

EMERGENCY AND FIRST AID PROCEDURES:

| | |
|----------------------|------------------------------------|
| EYE CONTACT: | Flush with water for 15-20 minutes |
| SKIN CONTACT: | Wash with soap and water |
| INHALATION: | Remove to fresh air |
| SWALLOWING: | Do not induce vomiting |

IN ALL CASES SEEK MEDICAL ATTENTION IF DISCOMFORT PERSISTS

| | |
|-------------------------|--|
| REACTIVITY DATA: | INCOMPATIBILITIES: Strong oxidizers |
| | Hazardous decomposition product |
| | Product is considered unstable |

| | |
|--------------------------------|---|
| SPILL OR LEAK PROCEDURE | Contain spill and shut off all sources of possible ignition Absorb on fire retardant material, sand or earth. Follow State or Local Authority regulations for disposal. |
|--------------------------------|---|

STORAGE AND HANDLING PROCEDURE

Not defined as Dangerous Goods for transport by road or rail.

Store away from heat, oxidizing agents, foodstuffs and clothing. No health risks are expected as a result of normal handling.

REFERENCE:

ISSUE DATE:
April 2005

FOR INFORMATION CONTACT:

Synforce (Aust.) Pty Ltd, P.O. Box 7181, Urangan, Hervey Bay, QLD. 4655
Telephone 07-41253531 Fax 07-41253521

Where the information provided in this bulletin indicates a potential hazard, adequate warning should be given to all

