



## Platinum 530, 5w/30, Low SAPS

Product code s2205, Sept 1, 2008  
revised Dec 2017

### DESCRIPTION

Platinum 530 is a Low SAPS SAE 5W/30 full synthetic high performance diesel and petrol engine oil designed for maximum oil drain intervals whilst being fully compatible with the latest Diesel Particulate Filters and Catalytic Converters fitted to many engines.

Platinum 530 meets the latest low emission Euro V and Euro IV European specifications, especially for those requiring a Low SAPS lubricant.

Platinum 530 is formulated with Low SAPS meaning that the lubricant is formulated with lower levels of Sulphated Ash, Phosphorous and Sulphur than conventional engine oils.

Most engines fitted with diesel particulate filters require a low SAPS oil.

### APPLICATION

Platinum 530 Low SAPS is recommended for use in all types of modern engines found in the latest Passenger Cars, 4WD and light Commercial vehicles requiring the following specifications ...

*SAE 5w/30 ... API SN/CF ... ACEA C1/C2/C4-12, C4-16 ... MB 226.51 ... Renault RN0720 ...  
Jaguar Land Rover STJLR.03.5005 ... Ford WSS-M2C913-D ... VW 502.00, 504.00, 505.01, 507.00 ...  
BMW LL04 ... Peugeot Citroen E06-N3, D06-N3 ... GM Dexos2*

### Typical Properties

SAE	5w/30
Density, kg/Lt at 15 <sup>o</sup> C	0.86
Viscosity, cSt at 100 <sup>o</sup> C	9.6
at 40 <sup>o</sup> C	52.7
Viscosity Index	169
Sulphated Ash	<0.5
Total Base No (TBN)	7.44

