

ProSYN 1540

Product code s2735, Dec 10, 2017

DESCRIPTION

ProSYN 1540 is a Semi Synthetic, Full SAPS, SAE 15w/40, API SN/CF petrol and light load diesel engine oil, designed for maximum protection under both normal and severe operating conditions. ProSYN 1540 is not suitable for use in Vehicles fitted with a DPF

ProSYN 1540 provides the ultimate in protection and performance. This premium quality engine oil meets and exceeds API: SN/CF and is suited for all types of four stroke engines operating under the most severe and varied conditions, such as high temperature highway driving conditions or low temperature stop-start driving around town.

The levels of powerful dispersants and detergents of ProSYN 1540 maintain much cleaner engines under all service conditions. The special active dispersants inhibit formation of sludge especially under the constant cold temperature operation of urban motoring and the careful selection of thermally stable base oils, oxidation inhibitors, viscosity improvers and detergents enhance the high temperature performance of ProSYN 1540, this contributes to less oxidation and more protection from piston deposits compared to conventional engine oils.

SPECIFICATIONS:

ProSYN 1540 meets or exceeds the following:

API SN/CF ... ACEA A3/B3-12, A3/B4-12 ... MB 229.3 VW 501.01/505.00 ... Renault 0700/0710

Typical Properties

| Density, kg/Lt at 15 ⁰ C | 0.884 |
|-------------------------------------|-------|
| Viscosity, cSt at 100°C | 15.8 |
| at 40°C | 121.2 |
| Viscosity Index | 138 |
| Sulphated Ash | 1.1 |

