



Tractor MP

Product code s4282, June 10, 2004

Description

Synforce Tractor MP is a Super Tractor Universal Oil designed for Tractor Engines, Transmissions, Hydraulics, and final drives including those with wet brake systems.

Tractor MP has an engine viscosity rating of SAE 15W40 and a service rating API CF 4+, having the soot handling capabilities of a CH-4 making it suitable for use in naturally aspirated and turbo charged diesel and four stroke petrol engines.

Tractor MP as a transmission oil contains extreme pressure additives exceeding the requirements of API GL4, SAE 80w making it highly suitable for transmissions & final drives used in off-highway and agricultural machinery.

Tractor MP as a hydraulic oil offers full anti-wear protection for all types of hydraulic pumps and systems meeting the wear and compatibility standards of Dennison vane & piston pumps as well as other gear pumps. It also meets the requirements of compressor manufacturers including ZF TE M1 06, 07.

Characteristics;

- Protects gearbox and working components due to antifoaming properties
- Consistent Viscosity throughout working temperatures

Typical Properties;

Viscosity @ 40 deg. C, cst.	116.3
Viscosity @ 100 deg. C, cst	16.5
Density @ 15 deg. C	0.88
Viscosity Index	147.6

Meets or Exceeds;

API GL4	SAE 80w
API CF-4+/SG	SAE 15w/40
ISO 68	ZF TE M1 06, 07
Allison C-4	Caterpillar TO-2

