



Platinum 540, 5w/40, Low SAPS

Product code s2204, May 1st 2016

DESCRIPTION

Platinum 540 is a Low SAPS SAE 5W/40 full synthetic high performance diesel and petrol engine oil designed for maximum oil drain intervals whilst being fully compatible with the latest Diesel Particulate Filters and Catalytic Converters fitted to many engines.

Platinum 540 meets the latest low emission Euro V and Euro IV European specifications, especially for those requiring a Low SAPS lubricant.

Platinum 540 is formulated with Low SAPS meaning that the lubricant is formulated with lower levels of Sulphated Ash, Phosphorous and Sulphur than conventional engine oils.

Most engines fitted with diesel particulate filters (or traps) require a low SAPS oil.

APPLICATION

Platinum 540 Low SAPS is recommended for use in all types of modern engines found in the latest Passenger Cars, 4WD and light Commercial vehicles requiring the following specifications ...

ACEA 07/04	A3,A5, B3,B4,B5, C2, C3-07
API	SL/SM, CF
Mercedes Benz	229.31, 229.51
VW (petrol & diesel)	502.00, 504.00, 505.01, 507.00
BMW	Long Life 04
Peugeot Citroen	E06-N3, D06-N3
GM	Dexros 2
Ford	WSS-M2C913-C and WSS-M2C948-A & B

Typical Properties

SAE	5w/40
Density, kg/Lt at 15 ⁰ C	0.848
Viscosity, cSt at 100 ⁰ C	13
at 40 ⁰ C	81
Viscosity Index	152
Sulphated Ash	0.6
Total Base No (TBN)	7.44

